

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 58-190107

(43)Date of publication of application : 07.11.1983

(51)Int.Cl.

H03G 3/24
G11B 5/027
H03G 3/32
H04R 3/00

(21)Application number : 57-072728

(71)Applicant : TOSHIBA CORP

(22)Date of filing : 30.04.1982

(72)Inventor : NAKAJO HIRONORI

HAYASHI HISAO

SATO KEINOSUKE


MURAMATSU YASUHIRO

(54) AUTOMATIC TALK LINE DEVICE

(57)Abstract:

PURPOSE: To deliver automatically an external sound signal supplied from a built-in microphone to a headphone, by discriminating the level of the external sound signal.

CONSTITUTION: A built-in microphone 15 can collect external voices while a headphone 14 for reproduction of a main sound signal. The output of the microphone 15 is fed to a level discriminating circuit 17 via an amplifier 16 as well as to an amplifier 12 via a talk line circuit 18. The circuit 18 is disconnected and an attenuator circuit 11 is inactive when no external sound signal exists. Then the reproduced output signal given from a reproducing head 10 is supplied to the headphone 14 via amplifiers 12 and 13. When the external sound signal exceeds a prescribed level, the circuit 17 is actuated to invert a switching circuit 19. Thus the circuit 18 is connected. Then the external sound signal supplied from the microphone 15 is supplied automatically to the head 14.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

First Hit

L1: Entry 1 of 2

File: JPAB

Nov 7, 1983

PUB-NO: JP358190107A
DOCUMENT-IDENTIFIER: JP 58190107 A
TITLE: AUTOMATIC TALK LINE DEVICE

PUBN-DATE: November 7, 1983

INVENTOR-INFORMATION:

NAME

COUNTRY

NAKAJO, HIRONORI

HAYASHI, HISAO

SATO, KEINOSUKE

MURAMATSU, YASUHIRO

ASSIGNEE-INFORMATION:

NAME

COUNTRY

TOSHIBA CORP

APPL-NO: JP57072728

APPL-DATE: April 30, 1982

US-CL-CURRENT: 330/281

INT-CL (IPC): H03G 3/24; G11B 5/027; H03G 3/32; H04R 3/00

ABSTRACT:

PURPOSE: To deliver automatically an external sound signal supplied from a built-in microphone to a headphone, by discriminating the level of the external sound signal.

CONSTITUTION: A built-in microphone 15 can collect external voices while a headphone 14 for reproduction of a main sound signal. The output of the microphone 15 is fed to a level discriminating circuit 17 via an amplifier 16 as well as to an amplifier 12 via a talk line circuit 18. The circuit 18 is disconnected and an attenuator circuit 11 is inactive when no external sound signal exists. Then the reproduced output signal given from a reproducing head 10 is supplied to the headphone 14 via amplifiers 12 and 13. When the external sound signal exceeds a prescribed level, the circuit 17 is actuated to invert a switching circuit 19. Thus the circuit 18 is connected. Then the external sound signal supplied from the microphone 15 is supplied automatically to the head 14.

COPYRIGHT: (C)1983,JPO&Japio